



SPECIFICATION SHEET

UMACABLE HIGH QUALITY CAT5E U/UTP FLAT PATCH CABLE

ITEM NO.: UMNW2005




KEY FEATURES :

- High Quality CAT5E U/UTP Unshielded Flat Patch Cable
- The flat cable design makes the cabling flexible and easy at tight spaces
- Meets or exceeds TIA/EIA-568-C.2 and ISO/IEC 11801 Specification
- Provides outstanding transmission performance and low signal losses
- Tested to 350 MHz and support 1000 Base-T Gigabit Ethernet
- A wired Cat 5E patch cable is more reliable and secure than a wireless network for your internet connections
- Lifetime Warranty


UMACABLE HIGH QUALITY CAT5E U/UTP FLAT PATCH CABLE

100 Xiangyun Rd, High - Tech Zone, Ningbo, China 315040 | +86 574 87042335 | www.umacable.com


UMACABLE HIGH QUALITY CAT5E U/UTP FLAT PATCH CABLE



Diagram



Construction



Electrical Characteristics:

Conductor DC Resistance:	89 Ohm/km (maximum)
Insulation Resistance :	100 Ohm/km (minimum)
Dielectric Strength:	500 MV/m
Propagation Delay:	545ns/100m (maximum)
Delay Skew:	45ns/100m (maximum)

Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80℃
Operating Temperature Range	-20℃ - 80℃
Storage Temperature Range:	-25℃ - 85℃
Approvals:	RoHS, CE, UL Compliant

Conductors (4 pairs)

Conductor Type:	32AWG Bare Copper
Insulation:	HDPE
Color:	White-Orange/Orange, White-Green/Green White-Blue/Blue, White-Brown/Brown

Overall

Jacket:	PVC, LSZH, LDPE, CMX, C
OD:	1.5±0.2*6.2±0.2mm

Customized Parameters

Guage:	AWG 32, 30
Length:	1, 2, 3, 5, 10, 20, 30m
Color:	Customized
Package type:	PE bag, Zip bag, Box, Hang card, Blister