

SPECIFICATION SHEET

UMACABLE HIGH QUALITY USB 3.0 A MALE TO A MALE CABLE

ITEM NO.: UMUB2001







KEY FEATURES:

- Super Speed USB 3.0 A Male to A Male Cable
- Plug and play for keyboards, mice, modems and other USB peripherals
- Support Super speed USB 3.0 devices and the transfer rate reaches to 4.8 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps) and low speed USB 1.0 (1.5 Mbps)
- Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance
- Lifetime Warranty


UMACABLE HIGH QUALITY USB 3.0 A MALE TO A MALE CABLE



Diagram



Construction



Electrical Characteristics:

Nominal Velocity of Propagation: 4.8Gbps

Propagation Delay: 5.2ns/m(Max), 26ns/cable

Skew: 20ps/3.5m(max) Dielectric Strength: AC 500V/1 minute

Insulation Resistance: $10M\Omega$

Conductor 1 (2 pairs)

Conductor Type: 28AWG Bare Copper

Insulation: Foamed PE

Color: Blue/Yellow, Purple/Orange

Drain Wire: 28AWG Bare Copper Shield: Aluminum Foil+Mylar

100% Coverage

Voltage Rating: 30V 90mm Maximum Bend Radius: 80℃ **Temperature Rating:**

Physical Characteristics:

Approvals: **RoHS Compliant**

Packagte type: PE bag, Zip bag, Box, Hang card, Blister

Conduct 2 (1 core)

Conductor Type: 28AWG Bare Copper

Insulation: **HDPE** Color: Black

Shield: Aluminum Foil+Mylar

100% Coverage

Connector 1

Connector Type: USB 3.0 A Male PIN Construction: **Phosphor Copper**

Nickel Plating: Injection: 45P PVC

Connector 2

Connector Type: USB 3.0 A Male PIN Construction: **Phosphor Copper**

Nickel Plating: Injection: 45P PVC

Overall

Foil Shield: Aluminum Foil+Mylar

100% Coverage

Braided Shield: 16/5/0.12 Aluminum Magnesium

Jacket: PVC

OD: 5.5±0.2mm

Customized Parameters

AWG 28/28/28, 28/28/26, 28/28/24 Guage:

Length: 0.5, 1, 1.5, 1.8, 2, 3, 5m Color: Black or Customized

Customized Ferrite Core: Nylon Mesh: Customized

Packagte type: PE bag, Zip bag, Box, Hang card, Blister